



SE-MD10W

Mini 10× PTZ Camera



Features

- ◆ Vandal Resistance Mini PTZ , with Hitachi DSP Camera
- ◆ Pelco-P, D protocol auto sensing
- ◆ Camera ID, baudrate set via OSD Menu.
- ◆ 128 presets with title, 4 auto scan, 4 preset tours, 4 pattern tours.
- ◆ Auto park action to initiate any presets, scan, tour or pattern after a set time.
- ◆ 4 window blanking (privacy mask) zones.
- ◆ With real-time clock and scheduled function.
- ◆ Wall Mount bracket and Corner mount bracket selection.
- ◆ IP66 weather proof

Specification

Imaging sensor	1/4" Sony Super HAD CCD
Resolution	500 /570 lines
Effective Pixel (H X V)	768 (H) X 494 (V) NTSC 762 (H) X 582 (V) PAL
Video output	CVBS: 1.0Vp-p/75ohm
Zoom Length	3.8mm-38mm
Zoom	100 times (10x optical X 10xdigital)
Synchronization	Internal, VD-Lock
Illumination	Color 0.7 Lux B/W 0.02 Lux @ 50IRE, F1.8
S / N	≥50 db (AGC Off, Weight On)
White Balance	ATW/AWC/Manual (1800 °K ~ 10,500°K)
Gain Control	Normal, high, off selectable
Electronic shutter speed	Auto: NTSC(X128 ~ 1/60s~ 1/120,000s); PAL (X128 ~ 1/50s~ 1/120,000s) Sens-up and Sens-up Limit is selectable, Flickerless
Pan /Tilt rotation range	360 ° continuous rotation / 0 ~ 90 ° with auto-flip
Pan /Tilt speed	0.5° ~ 160°per second / 0.5° ~ 90° per second
Presets	128
Decoders	Built - in
Baud rate (RS485/422)	2400/4800/9600/19200 bps
ID range	1 ~ 254
Communication	RS485/422 Bus
Protocol	Pelco-P, D auto sensing
Degree of Protection	IP66, TVS1500W lightning proof, Surge-proof and wave-proof protection
Power Supply	DC12V/1.5A
Power consumption (W)	≤ 9 W
Operation Temperature	- 10°C ~ 50°C
Environmental Humidity	0 ~ 95% (non-condensing)
Dimensions with package	245 × 195 × 185 (mm)
Net weight	1.4 (kg) (without bracket)
Gross Weight	1.7 (kg) (without bracket)